(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 22 January 2004 (22.01.2004)

PCT

(10) International Publication Number WO 2004/007776 A3

(51) International Patent Classification7:

(21) International Application Number:

PCT/EP2003/007431

(22) International Filing Date:

9 July 2003 (09.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: MT2002A001526

11 July 2002 (11.07.2002)

- (71) Applicant (for all designated States except US): DANIELI & C. OFFICINE MECCANICHE S.P.A. [IT/IT]; Via Nazionale, 41, I-33042 Buttrio (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VECCHIET, Fabio [IT/IT]; Via Trieste, 19, I-33059 Villa Vicentina (IT). PAVLICEVIC, Milorad [HR/IT]; Via Maniago, 4/C, I-33100 Udine (IT). POLONI, Alfredo [IT/IT]; Via G. Paolini, 29, I-34070 Fogliano Redipuglia (IT).

- C21C 5/52 (74) Agent: GERVASI, Gemma; Notarbartolo & Gervasi S.p.A., Corso di Porta Vittoria, 9, I-20122 Milan (IT).
 - (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH. GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC. SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA. UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
 - (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

[Continued on next page]

(54) Title: INJECTOR-BURNER FOR METAL MELTING FURNACES



(57) Abstract: The following invention relates to an injector-burner for applications in the metalwork field, in particular for use in electric arc furnace melting processes having a frontal head with two series of holes arranged in two concentric crowns, the inner crown of holes used to feed fuel and the outer crown used to supply a supporter of combustion. A central hole is also provided, which is fitted with an oxygen injection nozzle. The holes of the two crowns are divided into groups separated by circular sectors without noles, in order to create a number of flames and are inclined in such a way as to give the gases supplied, and consequentially the flame generated, a rotation around the injector-burner axis. By regulating the flow-rates of the fuel and the supporter of combustion supplied to the various holes, the injector-burner is able to regulate the flame shape in burner mode and also in injection mode, thus guaranteeing optimum performance in all modes.